



Potenzalube SAE 15W/40 SL/CI-4

DESCRIPTION

Potenzalube SAE 15W/40 is a high grade, heavy duty diesel engine oil for use in both Diesel and Petrol engines. This product had been formulated using International approved additive packages to meet the latest specifications required for today's modern engines and is recommended for "mixed" fleet applications.

APPLICATIONS

A superior grade diesel engine oil containing detergents, dispersants, anti-wear, corrosion and oxidation inhibitors for both petrol and diesel engines where high a specification oil is recommended. This product has exceptional ability in reducing wear and deposits. Applications include the majority of trucks, busses, and off-highway equipment operating under the most severe operating conditions.

BENEFITS

- OEM approvals
- Extended drain intervals
- Reduced maintenance costs
- Multi-fleet applications (Petrol and Diesel)
- Protection from wear and deposits.

PERFORMANCE

- API SL/CI-4
- ACEA E7 -08 Issues 2
- ACEA A3/B3-10
- ACEA A3/B4-10
- MB229.1 (in XOM)
- MB 228-3 (blanket approval)
- Volvo VDS-3
- MAN M3275
- MTU Type 2



- MACK EO-M+
- Renault Trucks RLD-2
- Cummins CES 20076/77/78
- JASO DH-1
- Global DHD-1

TYPICAL PHYSICAL CHARACTERISTICS

T y p i c a l C h a r a c t e r i s t i c s	Values
Density (SG)	.885
Viscosity @ 40 Degrees C	117.7 cSt
Viscosity @ 100 Degrees C	15.71 cSt
Viscosity Index (VI)	142
Total Base Number (TBN)	10.6